

# Rotabroach™

## MEET OUR NEW PACKAGING

### Twist Lock Packaging Design

“Patented packaging concept with bayonet type twist lock closure technique”



Rotabroach are continually introducing innovative products to market, this commitment is shown through our latest packaging developments.

We are excited to announce that with immediate effect all cutter packaging will change to the newly patented packaging concept BLOCKPACK from Rose plastics with its impressive Twistlock system.

With our ever expanding cutter proposition this change in packaging design will not only bring all the advantages of Twistlock but will combine colour coded end caps aligned to our product selector chart, making product selection and identification much easier.


Further to customer feedback, we are now providing barcodes to our new cutter packaging to

help aid customer efficiency, allowing for easier stock management.

For further information on features and benefits please visit the website.



“Watch the video on the news page of our website.”



#### Rotabroach Raptor M2AL

- Mild Steel
- Structural Steel
- Aluminium
- Copper
- Brass



**Rotabroach**  
M2AL Raptor Cutter  
RAP220 Rotabroach Raptor Cutter  
22mm Diameter

**25mm D.O.C**

<b>M2AL Raptor Cutter</b>	
Size Range	11mm - 53mm / RAP110 - RAP530
Cutting Depth	25mm
Max Tensile Strength	e900N/mm <sup>2</sup>
Ideal For	Mild & Structural Steel


**Pilot Pins**  
SRA305 | RAP110 - RAP120  
SRA25 | RAP130 - RAP520

**Rotabroach**  
M2AL Raptor Cutter  
RAPL220 Rotabroach Raptor Cutter  
22mm Diameter

**50mm D.O.C**

<b>M2AL Raptor Cutter</b>	
Size Range	12mm - 65mm / RAPL120 - RAPL650
Cutting Depth	50mm
Max Tensile Strength	e900N/mm <sup>2</sup>
Ideal For	Mild & Structural Steel

**Pilot Pins**  
RA313 | RAPL130  
SRA50 | RAPL130 - RAPL650



#### Rotabroach Raptor TCT

- Construction Steel
- Stainless Steel
- High Strength Steel
- Cast Iron
- Fine Grain Steel



**Rotabroach**  
TCT Raptor Cutter  
CWCX22 Rotabroach Raptor Cutter  
22mm Diameter

**CWC 35mm D.O.C  
CWCX 75mm D.O.C**

<b>TCT Raptor Cutter</b>	
Size Range	18mm - 100mm / CWC18 - CWC100
Cutting Depth	75mm
Max Tensile Strength	e1400N/mm <sup>2</sup>
Ideal For	Constructional Steel, Stainless Steel, High Strength Steel


**Pilot Pins**  
SRA120 | CWC18 - CWC65  
SRA101 | CWC66 -

**Rotabroach**  
TCT Raptor Cutter  
CWCX22 Rotabroach Raptor Cutter  
22mm Diameter

**CWCL 50mm D.O.C  
CWCX 100mm D.O.C**

<b>TCT Raptor Cutter</b>	
Size Range	18mm - 100mm / CWC18 - CWC100
Cutting Depth	100mm
Max Tensile Strength	e1400N/mm <sup>2</sup>
Ideal For	Constructional Steel, Stainless Steel, High Strength Steel

**Pilot Pins**  
SRA122 | CWC18 - CWC65  
SRA103 | CWC66 -



#### Rotabroach Raptor CTCT

- Hardox
- Inox
- Inconel
- Cast Iron
- Fine Grain Steel
- Other Tough Alloys



**Rotabroach**  
CTCT Raptor Cutter  
CTCT22 Rotabroach Raptor Cutter  
22mm Diameter


**25mm D.O.C**

<b>CTCT Raptor Cutter</b>	
Size Range	18mm - 40mm / CTCT18 - CTCT40
Cutting Depth	75mm
Max Tensile Strength	e1800N/mm <sup>2</sup>
Ideal For	Super Tough Alloys

**Pilot Pins**  
SRA25 | CTCT18 - CTCT40

**Rotabroach**  
CTCT Raptor Cutter  
CTCT22 Rotabroach Raptor Cutter  
22mm Diameter

**NEW JUNE 2016**



#### Rotabroach Rail M2AL

- Rail Track



**Rotabroach**  
M2AL Rail Cutter  
SRCV220 Rotabroach Rail Cutter  
22mm Diameter

**25mm D.O.C**

<b>M2AL Rail Cutter</b>	
Size Range	13mm - 36mm / SRCV130 - SRCV360
Cutting Depth	25mm
Max Tensile Strength	e1100N/mm <sup>2</sup>
Ideal For	Mild & Structural Steel & Rail Track


**Pilot Pins**  
SRA25 | SRCV130 - SRCV360

**Rotabroach**  
M2AL Rail Cutter  
SRCV220 Rotabroach Rail Cutter  
22mm Diameter

**50mm D.O.C**

<b>M2AL Rail Cutter</b>	
Size Range	13mm - 36mm / SRCV130 - SRCV360
Cutting Depth	50mm
Max Tensile Strength	e1100N/mm <sup>2</sup>
Ideal For	Mild & Structural Steel & Rail Track

**Pilot Pins**  
SRA50 | SRCV130 - SRCV360



#### Rotabroach Rail TCT

- Rail Track



**Rotabroach**  
TCT Rail Cutter  
SCRWC22 Rotabroach Rail Cutter  
22mm Diameter

**25mm D.O.C**

<b>TCT Rail Cutter</b>	
Size Range	18mm - 36mm / SCRWC18 - SCRWC36
Cutting Depth	25mm
Max Tensile Strength	e1400N/mm <sup>2</sup>
Ideal For	Rail Track

**Pilot Pins**  
SRA25 | SCRWC18 - SCRWC36